














## KOMPAKT FLORESAN LAMBA TABLOSU

Tip	Tanım	Güç (W)	Ölçüler(mm)			Kap	Lamba		Güç (W)
			L1	L2	Ø		Tip	Tanım	
<b>TC</b>	Tek kompakt kendinden starterli(2pin) 	5	85	108	12,5	G23	29	0,180	BBM-C BBS-C
		7	115	138	12,5		42	0,175	
		9	145	168	12,5		56	0,170	
		11	215	238	12,5		68	0,155	
		13	154	177	12,5	GX23	60	0,285	
<b>TC-E</b>	Tek kompakt dıştan starterli(4pin) 	5	5	85	-	12,5	2G7	36	0,180
		7	115	-	12,5		45	0,175	BBM-C BBS-C
		9	145	-	12,5		60	0,170	
		11	215	-	12,5		90	0,155	
		13	154	-	12,5	2GX7	60	0,285	
<b>TC-D</b>	Çift kompakt kendinden starterli (2pin) 	10	10	95	118	12,5	G24d	67	0,190
		13	130	153	12,5		100	0,165	BBM-C BBS-C
		18	150	173	12,5		105	0,220	
		26							
<b>TC-DE</b>	Çift kompakt dıştan starterli(4 pin) 	10	95	118	12,5	G24q	67	0,190	BBM-C BBS-C
		13	130	153	12,5		100	0,165	
		18	150	173	12,5		105	0,220	
		26							

Tip	Tanım	Güç (W)	Ölçüler(mm)			Kap	Lamba		Güç (W)
			L1	L2	Ø		Tip	Tanım	
<b>TC-DD</b>	Kompakt 2D kendinden starterli(2pin) 	10	94	94	14	GR8	72	0,180	BBM-C BBS-C
		16	14	142	15		103	0,200	
		21	2						
		28							
		38							
<b>TC-DDE</b>	Kompakt 2D dıştan starterli(4pin) 	10	94	94	14	GR10q	72	0,180	BBM-C BBS-C
		7	16	142	142			0,200	
		9	21						
		11	28						
		13	38						
<b>TC-T</b>	Kompakt üçlü kendinden starterli(2pin) 	18	11	-	12	GX24d	100	0,220	BBM-C BBS-C
		26	4						
<b>TC-TE</b>	Kompakt üçlü dıştan starterli(4pin) 	18	11	-	12	GX24	100	0,220	BBM-C BBS-C
		26	4						
		32							

## LINEAR FLORESAN LAMBA TABLOSU

Tip	Tanım	Güç (W)	Ölçüler(mm)			Kap	Lamba		Güç (W)	
			L1	L2	Ø		Tip	Tanım		
<b>T</b>	Tubular 	4	136	-	16	G5	29	0,17	BBM-L BBM-S BBT-L BBM BBS	
		6	212	-	16		42	0,16		
		8	288	-	16		56	0,145		
		10	470	-	26		68	0,170		
		13	517	-	16		95	0,165		
<b>TL</b>	Tubular 	<b>18/20</b>	589,8	-	40,5	G13	57	0,37	BBM-L BBM-S BBT-L BBM BBS	
		<b>36/40</b>	1194,4	-	40,5		G13	101		0,43
		<b>58/65</b>	1500	-	40,5		G13	110		0,67
<b>TL'D</b>	Tubular 	15	437.4	-	28	G13	59	0.36	BBM-L BBM-S BBL-L BBM BBS	
		18	589.8	-	28		59	0.36		
		30	894.6	-	28		98	0.36		
		36	1199.4	-	28		103	0.44		
		58	1500	-	28		111	0.67		